

wilo

Pioneering for You

Compact

**Building services
residential,**

House hold applications.





WP Mini

**Self priming mini monobloc
(available in single phase only)**

Flow: upto 52 LPM

Head: upto 45 mts

Power: upto 0.75 kW (1HP)

Pipe Size 25 mm

Volt: 230 v

Applications

Water transfer in

- Bungalows
- Farm houses
- Apartments



MPM

**Non self priming centrifugal monobloc
(available in single phase and 3 phase)**

Flow: upto 2300 LPM

Head: upto 78 mts

Power: upto 30 HP

Applications

Water transfer in

- Bungalows / farm houses
- Apartments / hotels
- Curing at construction sites



WPO

**Open well submersible
(single phase)**

Flow: 740 LPM

Head: 33 mts

Power: upto 3HP

Applications

Water transfer in

- Bungalows
- Farm houses
- Apartments



MPO

Open well submersible (3 phase)

Flow: upto 1465 LPM

Head: upto 62 mts

Power: upto 10 HP

Applications

Water transfer in

- Bungalows
- Farm houses
- Apartments



MNCM

Self priming non clog pumpset

Flow: 1110 LPM

Head: 34 mts

Applications

Water transfer in

- De-watering from trenches and pits houses
- Sewage pumping



MNC

Self priming non clog pump (available with motor or engine on request)

Flow: 4446 LPM

Head: 34 mts

Applications

- De-watering from trenches and pits
- Sewage pumping



WJ

Self priming jet pump

Flow: 83LPM

Head: 50 mts

Applications

- Pumping water from wells
- Filling, pumping empty transferring by pumping, irrigation and sprinkling
- As emergency pump for overflows.



WBS

Borehole submersible pump (available in single and 3 phase)

Flow: 180 LPM

Head: 1207 ft

Applications

- Suitable for 4" borewell.
- Domestic household water supply.
- Water supply to high rise buildings, housing complex and villas.
- Farm houses, gardens and nurseries.
- Washing - garages, poultry farms, cattle farms, and stud farms.



PB Series

Inline booster

Flow: upto 80 LPM

Head: upto 19 mts

Power: upto 400 Watt

Applications

- Pressure boosting water transfer from roof tank to tap



PW

Peripheral in line booster

Flow: 40 LPM

Head: 45 mts

Power: upto 250 Watt

Applications

- Boosting water pressure at taps and showers
- Water supply for household use
- Water transfer for small machines and instruments
- Sprinkler systems
- Gardening and car washing



FWJ / HWJ

Single pump booster

Flow: upto 80 LPM

Head: upto 46 mts

Applications

Water transfer in

- Bungalows / farm houses
- Apartments / hostels



HMHIL/FMHIL

Single pump booster

Flow: upto 215 LPM

Head: upto 62 mts

Applications

Water transfer in

- Bungalows / farm houses
- Apartments / hostels



VMHIL

Domestic booster with VFD

Flow: 10 m³/hr

Head: 65 m

Applications

The pressure boosting pump with variable frequency drive is used to maintain the constant pressure in water supplies of

- Residential buildings
- Hotels
- Hospitals
- Water supply and distribution from a sump or a tank



MHIL - BC

Horizontal twin pump booster

Flow: upto 430 LPM

Head: upto 65 mts

Applications

Pressure boosting in

- Bungalows
- Farm houses
- Apartments and
- Hotels



MVI - BC

Vertical twin pump booster

Flow: upto 800 LPM

Head: upto 130 mts

Applications

Pressure boosting in

- Bungalows
- Farm houses
- Apartments and
- Hotels



TWI 5

Submersible booster

Flow: upto 266 LPM

Head: upto 88 mts

Applications

Pumping from

- Well
- Sump



PD

Portable de-watering Pump

Flow: 160 LPM

Head: 7.5 mts

Applications

- Clean public bath, water tanks
- Building basement, drainage of handy sewage facility
- Drainage to prevent flooding for small places



FAS

De-watering pump (SS/Cl)

Flow: upto 1000 LPM

Head: upto 30 mts

Solid passage: upto 16 mm

Applications

- Dewatering from residential buildings
- Commercial buildings
- Industry
- Hospitals



TMW

Portable de-watering Pump

Flow: upto 220 LPM

Head: upto 10 mts

Solid passage: upto 10 mm

Applications

- Dewatering from residential buildings
- Commercial buildings
- Industry
- Hospitals



STS / T

Sewage pump (SS/Cl)

Flow: upto 1500 LPM

Head: upto 32 mts

Solid passage: upto 65 mm

Applications

- Sewage disposal on residential buildings
- Commercial buildings
- Industry
- Small hospitals



MTS

Cutter pump

Flow: upto 266 LPM

Head: upto 38 mts

Solid passage: upto 10 mm

Applications

- Sewage from residential buildings
- Commercial buildings
- Industry
- Small hospitals



Star RS

Hot water circulatory with controller

Flow: 90 m³/hr

Head: 7.5 m

Applications

- Differential temperature control in forced circulation solar systems
- Hot water circulation in heat pump system and similar applications
- Return line temperature controller for maintaining set water temperature at all outlet taps



Authorised Dealer for

(Germany)

MEC WATER TECHNOLOGIES

Head Office:

15 - K, AMBANAGAR,
OPP. SAJAVAT SHOWROOM,
NEAR SOSYO CIRCLE,
UDHNA- MAGDALLA ROAD,
SURAT - PIN: 395002



+ 91 9825550445
+91 9375025333



info@mecwatertechnologies.com
www.mecwatertechnologies.com